

Ciężar krat wciskanych obramowanych i ocynkowanych ogniowo [kg/m²]

Oczko [mm]	Wymiar płaskownika nośnego [mm]																
	20x1,5	25x1,5	30x1,5	40x1,5	20x2	20x3	25x2	25x3	30x2	30x3	30x4	35x2	35x3	40x2	40x3	40x4	50x3
16x11					38	49	43	57	49	66	88	54	74	60	82	110	105
16x22					30	41	35	50	41	58	77	47	66	52	75	100	94
16x33					27	39	33	47	39	55	74	44	64	50	72	96	91
16x44					26	37	32	46	37	54	72	43	63	49	71	95	89
16x66					25	36	30	44	36	53	70	42	61	47	70	93	87
22x11					31	40	35	46	40	52	70	44	58	48	64	86	76
22x22	16	19	22	28	24	32	28	38	32	44	59	36	50	40	56	75	68
22x33	15	18	21	27	21	29	25	35	29	41	56	33	47	37	53	72	65
22x44	14	17	20	26	20	28	24	34	28	40	54	32	46	36	52	70	64
22x66	13	16	19	25	18	27	23	33	27	39	52	31	45	35	51	68	63
33x11					26	32	29	36	32	40	54	35	45	38	49	66	57
33x22	13	15	17	21	18	24	21	28	24	32	44	27	37	30	41	55	50
33x33	11	13	15	20	16	22	19	26	22	30	40	25	34	27	38	52	47
33x44	11	13	15	19	15	20	18	25	20	29	39	23	33	26	37	50	45
33x66	10	12	14	18	13	19	16	23	19	27	37	22	32	25	36	48	44
44x11					24	28	26	32	28	35	47	31	38	33	42	56	48
44x22	11	12	14	17	16	20	18	23	20	26	37	23	30	24	33	46	39
44x33	10	11	13	16	13	17	15	21	17	24	33	20	28	22	30	42	36
44x44	9	10	12	15	12	16	14	19	16	23	32	19	27	21	29	40	35
44x66	8	10	11	15	11	15	13	18	15	21	30	18	25	19	28	39	34
55x11					22	26	24	29	26	31	42	28	34	29	37	49	42
55x22	10	11	12	15	15	18	16	21	18	24	32	20	26	22	29	39	34
55x33	8	10	11	14	12	16	14	18	16	21	28	17	24	19	26	35	32
55x44	8	9	10	13	11	14	13	17	14	20	27	16	22	18	25	34	30
55x66	7	8	10	12	10	13	11	16	13	18	25	15	21	17	24	32	29
66x66	6	8	9	11	9	12	10	14	12	16	22	13	18	15	21	28	25
66x99					8	11	9	13	11	15	20	12	17	14	20	27	24